

**RADIATION HAZARD EXHIBITS**

FCC OET-65 RF Exposure Study - Satellite Uplink Facility  
**4.57m Ku Band Antenna - The Wellness Network, Melbourne, FL**

FCC Maximum Permissible Exposure Levels	Source	Units
Public/uncontrolled area exposure limit	47CFR §1.1310	1 mW/cm <sup>2</sup>
Occupational/controlled area exposure limit	47CFR §1.1310	5 mW/cm <sup>2</sup>

**Input Data**

Antenna Diameter	datasheet	457.0 cm
Antenna surface area	calculated	164030 cm <sup>2</sup>
Sub-reflector diameter	measured	74.000 cm
Sub-reflector area	calculated	4301 cm <sup>2</sup>
Feed flange diameter	measured	17.800 cm <sup>2</sup>
Feed flange area	calculated	249
Frequency	(entry)	14250 MHz
Wavelength (speed of light = 299,792,458 m/s)	calculated	2.104 cm
Transmit power at flange	Application	40000 milliwatts
Antenna gain	datasheet	54.9 dBi
Antenna gain factor	calculated	309030
Height of base of antenna above ground	measured	0.68 m
Height of center of antenna above ground	measured	2.3 m
Minimum Elevation Angle	(entry)	20 degrees
Minimum Elevation Angle	calculated	0.34907 radians

**Results calculated using FCC Bulletin OET-65 (Edition 97-01 August 1997)**

		FCC Maximum Permissible Exposure (MPE)	
		Uncontrolled	Controlled
Maximum power density at antenna surface	Eq. 11 Pg 27	0.97543358 mW/cm <sup>2</sup>	Below FCC MPE
Power density at subreflector	Eq. 11 Pg 27	37.202032 mW/cm <sup>2</sup>	Potential Hazard
Power density at feed flange	Eq. 11 Pg 27	642.969092 mW/cm <sup>2</sup>	Potential Hazard
Extent of near-field	Eq. 12 Pg 27	24818 cm	Potential Hazard
Maximum near-field power density	Eq. 13 Pg 28	0.64725771 mW/cm <sup>2</sup>	Below FCC MPE
Aperture efficiency	Eq. 14 Pg 28	0.66355898	Below FCC MPE
Distance to beginning of far-field	Eq. 16 Pg 29	59563.1712 cm	
Power density at end of the transition region	Eq. 17 Pg 29	0.26969071 mW/cm <sup>2</sup>	Below FCC MPE
Maximum far-field power density	Eq. 18 Pg 29	0.277 mW/cm <sup>2</sup>	Below FCC MPE

**Main Beam Far-field region safe exposure distances**

Minimum distance for public/uncontrolled exposure	Eq. 18 Pg 29	313.635391	meters
Height at minimum antenna elevation angle	calculated	109.569622	meters
Horizontal distance	calculated	294.720863	meters
Minimum distance for occupational/controlled exposure	Eq. 18 Pg 29	140.262011	meters
Height at minimum antenna elevation angle	calculated	50.2724331	meters
Horizontal distance	calculated	131.803177	meters

**Off-Axis Near Field/Transition Region safe exposure distances from antenna**

(20 dB reduction in power density at distances greater than one antenna diameter from the main beam center.)	OET-65 Pg 30		
Maximum off-axis near field power density	Eq. 13 Pg 28	0.0065 mW/cm <sup>2</sup>	Below FCC MPE
Public/uncontrolled exposure off-axis distance	Diam/or Eq 17	4.57 meters	Below FCC MPE
Occupational/controlled exposure off-axis distance	Diam/or Eq 17	4.57 meters	Below FCC MPE

**Off-Axis Far Field safe exposure distances from the antenna**

(Based on side lobe attenuation required by FCC 25.209(a)(2))			
Angle off main beam axis (1 to 48 degrees)	(entry)	20 degree(s)	
Off-axis antenna gain factor	OET-65 Pg 30*	1	
Minimum distance for uncontrolled MPE limit	calculated	0.53105264 meters	Not valid if distance less the start of the far field

Minimum distance for public/uncontrolled exposure

Eq. 18 Pg 29 \*\* 595.631712 meters

\* Gain converted from dBi to linear multiple

\*\* If calculated distance is less than the start of the far field region, the distance to the start of the far field region is used.

Prepared by Jim Lyons - TWN, 11/22/2016

FCC OET-65 RF Exposure Study - Satellite Uplink Facility  
**2.4m Ku Band Antenna - The Wellness Network, Melbourne, FL**

FCC Maximum Permissible Exposure Levels	Source	Units
Public/uncontrolled area exposure limit	47CFR §1.1310	1 mW/cm <sup>2</sup>
Occupational/controlled area exposure limit	47CFR §1.1310	5 mW/cm <sup>2</sup>

**Input Data**

Antenna Diameter	datasheet	240.0	cm
Antenna surface area	calculated	45239	cm <sup>2</sup>
Sub-reflector diameter	measured	24.000	cm
Sub-reflector area	calculated	11	cm <sup>2</sup>
Feed flange diameter	measured	8.000	cm <sup>2</sup>
Feed flange area	calculated	50	
Frequency	(entry)	14250	MHz
Wavelength (speed of light = 299,792,458 m/s)	calculated	2.104	cm
Transmit power at flange	Application	9170	milliwatts
Antenna gain	datasheet	48.9	dBi
Antenna gain factor	calculated	77625	
Height of base of antenna above ground	measured	0.68	m
Height of center of antenna above ground	measured	2.3	m
Minimum Elevation Angle	(entry)	20	degrees
Minimum Elevation Angle	calculated	0.34907	radians

**Results calculated using FCC Bulletin OET-65 (Edition 97-01 August 1997)**

		FCC Maximum Permissible Exposure (MPE)	
		Uncontrolled	Controlled
Maximum power density at antenna surface	Eq. 11 Pg 27	0.81080602	mW/cm <sup>2</sup>
Power density at subreflector	Eq. 11 Pg 27	3334.54545	mW/cm <sup>2</sup>
Power density at feed flange	Eq. 11 Pg 27	729.725414	mW/cm <sup>2</sup>
Extent of near-field	Eq. 12 Pg 27	6845	cm
Maximum near-field power density	Eq. 13 Pg 28	0.49001166	mW/cm <sup>2</sup>
Aperture efficiency	Eq. 14 Pg 28	0.60435128	
Distance to beginning of far-field	Eq. 16 Pg 29	16427.3646	cm
Power density at end of the transition region	Eq. 17 Pg 29	0.20417152	mW/cm <sup>2</sup>
Maximum far-field power density	Eq. 18 Pg 29	0.210	mW/cm <sup>2</sup>

**Main Beam Far-field region safe exposure distances**

Minimum distance for public/uncontrolled exposure	Eq. 18 Pg 29	75.2626899	meters
Height at minimum antenna elevation angle	calculated	28.041356	meters
Horizontal distance	calculated	70.7237943	meters
Minimum distance for occupational/controlled exposure	Eq. 18 Pg 29	33.6584981	meters
Height at minimum antenna elevation angle	calculated	13.8118844	meters
Horizontal distance	calculated	31.6286423	meters

**Off-Axis Near Field/Transition Region safe exposure distances from antenna**

(20 dB reduction in power density at distances greater than one antenna diameter from the main beam center.)	OET-65 Pg 30		
Maximum off-axis near field power density	Eq. 13 Pg 28	0.0049	mW/cm <sup>2</sup>
Public/uncontrolled exposure off-axis distance	Diam/or Eq 17	2.4	meters
Occupational/controlled exposure off-axis distance	Diam/or Eq 17	2.4	meters

**Off-Axis Far Field safe exposure distances from the antenna**

(Based on side lobe attenuation required by FCC 25.209(a)(2))			
Angle off main beam axis (1 to 48 degrees)	(entry)	20	degree(s)
Off-axis antenna gain factor	OET-65 Pg 30*	1	
Minimum distance for uncontrolled MPE limit	calculated	0.25426831	meters
Minimum distance for public/uncontrolled exposure	Eq. 18 Pg 29 **	164.273646	meters

\* Gain converted from dBi to linear multiple

\*\* If calculated distance is less than the start of the far field region, the distance to the start of the far field region is used.

**Not valid if distance less the start of the far field**