REQUEST FOR SPECIAL TEMPORARY AUTHORITY

By this application, SES Americom, Inc. ("SES") respectfully requests special

temporary authority ("STA") for a period of 60 days starting from 13<sup>th</sup> April, 2019 to operate the

earth station with call sign #E190099, on non-interference and unprotected basis as the

application for permanent license for the station is in pending. The carriers in Ku band

frequency (14,000-14,500 MHz) will be operated within the EIRP limit as specified in the

license application. The antenna will communicate with NSS-11which has license granted on

02/26/19 by FCC to operate at 176E longitude with reference to the File# SAT-PPL-20180815-

00062 and call sign # S3037.

NSS-11 downlink (space to earth) operates in the frequency range 12,250 MHz to 12,750MHz.

SES seeks a waiver to permit the earth station to receive the signal in this frequency band on an

unprotected, non-interference basis.

The technical details of the proposed operations are provided below. The earth station will be

operated in compliance with the Commission's radiation hazard limits and the antenna

performance will comply with the gain patterns as specified in section 25.209 (a2) and (b).

**Site Details** 

**Contact Information:** 

Kevin Baker 1808-638-0073 **Address:** 

58-350 Kamehameha Highway, Comsat Rd, Haleiwa, Honolulu, HI

**Geographic Coordinates:** 

Latitude: 21 40' 14.88"N Longitude: 158deg 1' 55.72"W

**Site Elevation:** 

140.0 meters

## **Antenna Details**

Antenna ID: Temp 8.1K

Manufacture/Model: Vertex Comm/8.1m Cassegrain

Antenna Size: 8.1 meters

Antenna Gain Transmit: 59.8 dBi at 14.25 GHz Antenna Gain Receive: 58.5 dBi at 11.95 GHz

Height Above Ground Level: 9.0 meters
Height Above Sea Level: 149 meters
Total Input Power at the Flange: 350 watts
Total EIRP for all Carriers: 85.24 dBW

## **Operational Details**

Frequency (MHz)	Transmit/ Receive	Polarization	Emissions Designator	Max EIRP per Carrier (dBW)	Max EIRP Density per Carrier (dBW/4kHz)
12250-12750	R	Horizontal and Vertical	36M0G7W	0.0	0.0
12250-12750	R	Horizontal and Vertical	64K0G7W	0.0	0.0
14000-14500	Т	Horizontal and Vertical	36M0G7W	85.24	45.69
14000-14500	Т	Horizontal and Vertical	64K0G7W	57.84	45.8