Exhibit 2: Earth Station Technical Information for STA Request

GUSA Licensee LLC (together with its parent Globalstar, Inc., ("Globalstar")) is seeking a 60-day Special Temporary Authority ("STA") in order to test and validate two waveforms for use in conjunction with Globalstar's licensed gateway earth station at Clifton, Texas, with the following parameters:

File No.: SES-MFS-20091221-01608

Call Sign: E000342 (CLFN-2)

STA term: April 10, 2020 to June 9, 2020

Location: Clifton, Texas

Latitude: 31° 47′ 57.5″ N

Longitude: 97° 36' 44.7" W

Transmit frequency: 5091 – 5250 MHz

Receive frequency: 6875 – 7055 MHz

Polarization: RHCP & LHCP

Antenna Size: 5.5 m

Gain: Tx: 47.6 dBi at 5.150 GHz

Rx: 50.2 dBi at 6.975 GHz

Max. antenna height: 28.5 feet above ground level

Necessary Bandwidth: Transmit bandwidth is 159 MHz

Receive bandwidth is 180 MHz

Maximum carrier bandwidth is 2.5 MHz

Maximum carrier bandwidth for test waveforms is 2 MHz for transmit and

200 KHz for receive

Carrier: See final four rows of table below, for carriers with emission designators

200KG7D, 20K0G7D, 2M00G7D, and 200KG7D

| Ето сугот от | T/D Mada & | Emission | Mayimayım | Maximayan | Madulation |
|--------------------|---------------------|---|----------------|------------------------|-------------------------|
| Frequency | T/R Mode & | Emission Designation | <u>Maximum</u> | Maximum EIDD Danaitre | <u>Modulation</u> |
| Band (MHz) | <u>Polarization</u> | <u>Designator</u> | EIRP | EIRP Density | |
| 5001 5002 | T. LUCD | ZCKOE2D | (dBW) | (dBW/4kHz) | TN 1 ' |
| 5091 – 5092 | Tx- LHCP | 76K0F2D | 68 | 55.2 | FM subcarrier on |
| | | | | | telecommand |
| | | | | | carrier |
| 6875.95 – | Rx – LHCP | 7K00G1D | | | Telemetry carrier |
| 6877.15 | | | | | |
| 5096 - 5250 | Tx - L/RHCP | 1M23XXX | 59 | 34.1 | White noise |
| | | | | | modulated carrier |
| | | | | | for testing |
| 6900 - 7055 | Rx - L/RHCP | 1M23XXX | | | White noise |
| | | | | | modulated carrier |
| | | | | | for testing |
| 5096 - 5250 | Tx – L/RHCP | N0N | 59 | 59 | Unmodulated CW |
| | | | | | for testing |
| 6900 – 7055 | Rx – L/RHCP | NON | | | Unmodulated CW |
| | | | | | for testing |
| 5096 - 5250 | Tx – L/RHCP | 1M23G7W | 55 | 30.1 | CDMA/voice and |
| | | | | | data |
| 6900 – 7055 | Rx – L/RHCP | 1M23G7W | | | CDMA/voice and |
| 0,000 1,022 | Tex Enterer | 11,125 67 11 | | | data |
| 5096 - 5250 | Tx – L/RHCP | 1M23G2W | 55 | 30.1 | CDMA/for single- |
| 3070 3230 | IX LIMICI | 11012502 00 | | 30.1 | carrier AMSS. |
| 6900 – 7055 | Rx – L/RHCP | 1M23G2W | | | CDMA/for single- |
| 0700 - 7033 | | 11V125G2 VV | | | carrier AMSS |
| 6900 – 7055 | Rx – L/RHCP | 2M50G2D | | | Direct sequence |
| 0900 - 7033 | KX – L/KIICI | 21VI30G2D | | | CDMA for single- |
| | | | | | _ |
| | | | | | carrier telemetry data |
| 5096 – 5250 | Tx – L/RHCP | 2M46G7W | 55 | 27.1 | CDMA/voice and |
| 3090 - 3230 | IX – L/RHCP | 2M40G/W | 33 | 27.1 | |
| (000 7077 | D. I./DIIGD | 2) (4) (67) | | | data |
| 6900 – 7055 | Rx - L/RHCP | 2M46G7W | | | CDMA/voice and |
| 5006 5050 | T. I /DIIGD | 2) (4 ((((((((((((((((((| | 27.1 | data |
| 5096 – 5250 | Tx – L/RHCP | 2M46G2W | 55 | 27.1 | CDMA/for single- |
| 6000 ==== | | 03.51.55: | | | carrier AMSS. |
| 6900 - 7055 | Rx - L/RHCP | 2M46G2W | | | CDMA/for single- |
| | <u> </u> | | | | carrier AMSS |
| 5091.38 - | Tx- LHCP | 40K0G2D | 68 | 58 | Telecommand |
| 5091.62 | | | | | carrier |
| 6875.9 – 6879.1 | Rx – LHCP | 70K0G7D | | | Telemetry carrier |
| 5096 - 5250 | Tx – L/RHCP | 200KG7D | 68 | 51 | Burst mode packet |
| | | | | | data with $\pi/2$ -BPSK |
| | | | | | modulation |
| | L | l . | _1 | 1 | |

GUSA Licensee LLC Page 3 of 4

| 6900 – 7055 | Rx – L/RHCP | 20K0G7D | | | Burst mode packet data with BPSK modulation |
|-------------|-------------|---------|----|----|---|
| 5096 – 5250 | Tx – L/RHCP | 2M00G7D | 68 | 41 | Burst mode packet data with π/2-BPSK modulation |
| 6900 – 7055 | Rx – L/RHCP | 200KG7D | | | Burst mode packet data with BPSK modulation |

Maximum EIRP: 68 dBW (for all carriers combined)

Maximum EIRP Density: 51 dBW/4 KHz

Satellite: S2115 (U.S.-licensed Globalstar Big LEO MSS system)

Orbital Location: NGSO (1414 km altitude, 52 degree inclination)

Elevation Angle (E/W): 10 degrees to 90 degrees

Azimuth (E/W): 0 degrees to 360 degrees

Satellite: HIBLEO-X GLOBALSTAR 2.0 (French-licensed Globalstar Big LEO

MSS system)

Orbital Location: NGSO (1414 km altitude, 52 degree inclination)

Elevation Angle (E/W): 10 degrees to 90 degrees

Azimuth (E/W): 0 degrees to 360 degrees

NOTE: The telecommand / telemetry carrier with designator 40K0G2D/70K0G7D are for GLOBALSTAR 2.0 satellites while the telecommand / telemetry carrier with designator 76K0F2D/7K00G1D are for current Globalstar satellites (Call Sign S2115).

<u>Information on MLS Sites</u>

For the Clifton, Texas, Globalstar gateway site, there are four potential MLS sites, i.e., Category III airports, within the 200 nautical mile coordination distance. The Clifton site is located at 31-48 06 N, 97-36-45 W. The airports are:

| | T |
|-----|---|
| IAH | Houston – George Bush International Airport, |
| | approximately 163 nautical miles from Clifton |
| AUS | Austin – Bergstrom International Airport, |
| | approximately 91 nautical miles away |
| DFW | Dallas/Ft. Worth International Airport, |
| | approximately 71 nautical miles away |
| AFW | Ft. Worth Alliance Field, approximately 68 |
| | nautical miles away |

Based on a directory used for MLS coordination purposes, and to the best of its knowledge, GUSA believes that MLS is not active at any of those sites and will not be active during the requested 60-day STA period.