Exhibit 2: Earth Station Technical Information for STA Extension Request

GUSA Licensee LLC (together with its parent Globalstar, Inc., ("Globalstar")) is seeking a 60day extension of its existing Special Temporary Authority ("STA"), in order to continue to operate a second-generation feeder link antenna at Globalstar's gateway earth station facility at Clifton, Texas. Under the proposed STA extension, Globalstar will continue to use this earth station antenna to test and validate two new waveforms and to carry commercial mobile satellite service traffic. This antenna will have the following parameters:

| Proposed STA term: | November 23, 2020 to January 22, 2021 |
|----------------------|--|
| Location: | Clifton, Texas |
| Latitude: | 31° 48' 2.1492" N |
| Longitude: | 97 ° 36' 44.3736" W |
| Transmit frequency: | 5091 – 5250 MHz |
| Receive frequency: | 6875 – 7055 MHz |
| Polarization: | RHCP & LHCP |
| Antenna Size: | 6 meters |
| Gain: | Tx: 47.5 dBi at 5.150 GHz Rx: 51.2 dBi at 6.975 GHz |
| Max. antenna height: | 28.5 feet above ground level |
| Necessary Bandwidth: | Transmit bandwidth is 159 MHz Receive bandwidth is 180 MHz Maximum carrier bandwidth is 2.5 MHz Maximum carrier bandwidth for test waveforms is 4.5 MHz for transmit and 200 KHz for receive |
| Carrier: | |

GUSA Licensee LLC Page 2 of 4

| <u>Frequency</u> Band (MHz) | <u>T/R Mode &</u> <u>Polarization</u> | Emission Designator | Maximum EIRP | <u>Maximum</u> <u>EIRP</u> | Modulation |
|--------------------------------|--|------------------------|-----------------|-------------------------------|---|
| | | | (<u>dBW)</u> | <u>Density</u> (dBW/4kHz) | |
| 5091 - 5092 | Tx- LHCP | 76K0F2D | 68 | 55.2 | FM subcarrier on |
| | | | | | telecommand carrier |
| 6875.95 – 6877.15 | Rx – LHCP | 7K00G1D | | | Telemetry carrier |
| 5096 - 5250 | Tx – L/RHCP | 1M23XXX | 59 | 34.1 | White noise modulated carrier for testing |
| 6900 - 7055 | Rx – L/RHCP | 1M23XXX | | | White noise modulated carrier for testing |
| 5096 - 5250 | Tx – L/RHCP | N0N | 59 | 59 | Unmodulated CW for testing |
| 6900 - 7055 | Rx – L/RHCP | N0N | | | Unmodulated CW for testing |
| 5096 - 5250 | Tx – L/RHCP | 1M23G7W | 55 | 30.1 | CDMA/voice and data |
| 6900 - 7055 | Rx – L/RHCP | 1M23G7W | | | CDMA/voice and data |
| 5096 - 5250 | Tx – L/RHCP | 1M23G2W | 55 | 30.1 | CDMA/for single-carrier AMSS |
| 6900 - 7055 | Rx – L/RHCP | 1M23G2W | | | CDMA/for single-carrier AMSS |
| 6900 - 7055 | Rx – L/RHCP | 2M50G2D | | | Direct sequence CDMA for single-carrier |
| | | | | | telemetry data |
| 6900 - 7055 | Rx – L/RHCP | 2M50G7D | | | Direct sequence CDMA for single-carrier |
| | | | | | telemetry data |
| 5096 - 5250 | Tx – L/RHCP | 2M46G7W | 55 | 27.1 | CDMA/voice and data |
| 6900 - 7055 | Rx – L/RHCP | 2M46G7W | | | CDMA/voice and data |
| 5096 - 5250 | Tx – L/RHCP | 2M46G2W | 55 | 27.1 | CDMA/for single-carrier AMSS |
| 6900 - 7055 | Rx – L/RHCP | 2M46G2W | | | CDMA/for single-carrier AMSS |

GUSA Licensee LLC Page 3 of 4

| 5091.38 - 5091.62 | Tx- LHCP | 40K0G2D | 68 | 58 | Telecommand carrier |
|----------------------|-------------|---------|----|------|--|
| 6875.9 – 6879.1 | Rx – LHCP | 70K0G7D | | | Telemetry carrier |
| 5096 - 5250 | Tx – L/RHCP | 200KG7D | 68 | 51 | Burst mode packet data with $\pi/2$ -BPSK modulation |
| 6900 - 7055 | Rx – L/RHCP | 20K0G7D | | | Burst mode packet data with BPSK modulation |
| 5096 - 5250 | Tx – L/RHCP | 4M50G7D | 68 | 37.5 | Burst mode packet data with $\pi/2$ -BPSK modulation |
| 6900 - 7055 | Rx – L/RHCP | 200KG7D | | | Burst mode packet data with BPSK modulation |

Maximum EIRP: 68.4 dBW (for all carriers combined)

Maximum EIRP Density: 51 dBW/4Hz

Satellite: S2115 (U.S.-licensed Globalstar Big LEO MSS system)

Orbital Location: NGSO (1414 km altitude, 52 degree inclination)

Elevation Angle (E/W): 5 degrees to 90 degrees

Azimuth (E/W): 0 degrees to 360 degrees

Satellite: HIBLEO-X GLOBALSTAR 2.0 (French-licensed Globalstar Big LEO MSS system)

Orbital Location: NGSO (1414 km altitude, 52 degree inclination)

Elevation Angle (E/W): 5 degrees to 90 degrees

Azimuth (E/W): 0 degrees to 360 degrees

NOTE: The telecommand / telemetry carrier with designator 40K0G2D/70K0G7D are for GLOBALSTAR 2.0 satellites while the telecommand / telemetry carrier with designator 76K0F2D/7K00G1D are for current Globalstar satellites (Call Sign S2115).

GUSA Licensee LLC Page 4 of 4

Information on MLS Sites

For the Clifton, Texas, Globalstar gateway site, there are four potential MLS sites, i.e., Category III airports, within the 200 nautical mile coordination distance. The Clifton site is located at 31-48-06 N, 97-36-45 W. The airports are:

| IAH | Houston – George Bush International Airport, |
|-----|---|
| | approximately 163 nautical miles from Clifton |
| AUS | Austin – Bergstrom International Airport, |
| | approximately 91 nautical miles away |
| DFW | Dallas/Ft. Worth International Airport, |
| | approximately 71 nautical miles away |
| AFW | Ft. Worth Alliance Field, approximately 68 |
| | nautical miles away |

Based on a directory used for MLS coordination purposes, and to the best of its knowledge, GUSA believes that MLS is not active at any of those sites and will not be active during the requested 60-day extension of the current STA period.