Exhibit 2: Earth Station Technical Information for STA Request

GUSA Licensee LLC (together with its parent Globalstar, Inc., ("Globalstar")) is seeking a 60-day extension of its existing Special Temporary Authority ("STA") in order to continue to operate a second-generation feeder link antenna at Globalstar's gateway earth station facility at Clifton, Texas. Under the proposed STA extension, Globalstar will continue to use this earth station antenna to test and validate a new waveform. Grant of this STA extension will allow Globalstar to operate this earth station antenna while the application for permanent authority for this antenna remains pending. This antenna will have the following parameters:

File No.: SES-STA-20210722-01266

Call Sign: E970199 (CLFN-1)

STA term: December 15, 2021 to February 13, 2022

Location: Clifton, Texas

Latitude: 31° 48′ 0.2" N

Longitude: 97° 36' 44.3" W

Transmit frequency: 5091 – 5250 MHz

Receive frequency: 6875 – 7055 MHz

Polarization: RHCP & LHCP

Antenna Size: 6 m

Gain: Tx: 47.5 dBi at 5.150 GHz

Rx: 51.2 dBi at 6.975 GHz

Max. antenna height: 28.5 feet above ground level

Necessary Bandwidth: Transmit bandwidth is 159 MHz

Receive bandwidth is 180 MHz

Maximum carrier bandwidth is 2.5 MHz

Maximum carrier bandwidth for test waveforms is 4.5 MHz for transmit

and 200 KHz for receive

Carrier: See table below, including final four rows for new waveforms

Frequency	T/R Mode &	Emission	Maximum	Maximum	Modulation
Band (MHz)	Polarization	Designator Designator	EIRP	EIRP Density	Modulation
Build (WHZ)	<u>r orarization</u>	<u>Designator</u>	(dBW)	(dBW/4kHz)	
5091 - 5092	Tx- LHCP	76K0F2D	68	55.2	FM subcarrier on
0071 0072	111 21101	, 01101 22		00.2	telecommand
					carrier
6875.95 –	Rx – LHCP	7K00G1D			Telemetry carrier
6877.15		71100012			
5096 – 5250	Tx – L/RHCP	1M23XXX	59	34.1	White noise
					modulated carrier
					for testing
6900 – 7055	Rx – L/RHCP	1M23XXX			White noise
0,000,000					modulated carrier
					for testing
5096 – 5250	Tx – L/RHCP	NON	59	59	Unmodulated CW
2070 2220		11011			for testing
6900 – 7055	Rx – L/RHCP	NON			Unmodulated CW
0700 7033	IX LITTEI	11011			for testing
5096 - 5250	Tx – L/RHCP	1M23G7W	55	30.1	CDMA/voice and
3070 3230	TX L/IGICI	11112507 11		30.1	data
6900 – 7055	Rx – L/RHCP	1M23G7W			CDMA/voice and
0700 7033	IX L/IXITCI	1111230711			data
5096 - 5250	Tx – L/RHCP	1M23G2W	55	30.1	CDMA/for single-
3070 - 3230		11V123G2 VV	33	30.1	carrier AMSS.
6900 – 7055	Rx – L/RHCP	1M23G2W			CDMA/for single-
0700 - 7033	KA – L/KIICI	11V123G2 VV			carrier AMSS
6900 – 7055	Rx – L/RHCP	2M50G7D			Direct sequence
0900 - 7033	KX – L/KIICI	21VI3007D			CDMA for single-
					carrier telemetry
					data
6900 – 7055	Rx – L/RHCP	2M50G2D			Direct sequence
0700 - 7033	KA – L/KIICI	21VI30G2D			CDMA for single-
					carrier telemetry
					data
5096 – 5250	Tx – L/RHCP	2M46G7W	55	27.1	CDMA/voice and
3070 - 3230		21 V14 0 G / VV	33	27.1	data
6900 – 7055	Rx – L/RHCP	2M46G7W			CDMA/voice and
0700 - 7033		2101400700			data
5096 – 5250	Tx – L/RHCP	2M46G2W	55	27.1	CDMA/for single-
3070 - 3230	IA - L/MICI	2111700211		27.1	carrier AMSS.
6900 – 7055	Rx – L/RHCP	2M46G2W			CDMA/for single-
0700 - 7033	KA - L/KIICF	2111400211			carrier AMSS
5091.38 -	Tx- LHCP	40K0G2D	68	58	Telecommand
5091.62	IA- LIICE	+01X0U2D	00	30	carrier
6875.9 –	Rx – LHCP	70K0G7D			Telemetry carrier
6879.1	KA – LHCP	/UKUU/D			reterried y carrier
00/9.1					

5096 – 5250	Tx – L/RHCP	4M50G7D	68	37.5	Burst mode packet data with $\pi/2$ -BPSK modulation
6900 – 7055	Rx – L/RHCP	200KG7D			Burst mode packet data with BPSK modulation
6900 – 7055	Rx – L/RHCP	230KG7D			Burst mode packet data with BPSK modulation
6900 – 7055	Rx – L/RHCP	280KG7D			Burst mode packet data with BPSK modulation

Maximum EIRP: 68.4 dBW (for all carriers combined)

Maximum EIRP Density: 51 dBW/4 KHz

Satellite: S2115 (U.S.-licensed Globalstar Big LEO MSS system)

Orbital Location: NGSO (1414 km altitude, 52 degree inclination)

Elevation Angle (E/W): 5 degrees to 90 degrees

Azimuth (E/W): 0 degrees to 360 degrees

Satellite: HIBLEO-X GLOBALSTAR 2.0 (French-licensed Globalstar Big LEO

MSS system)

Orbital Location: NGSO (1414 km altitude, 52 degree inclination)

Elevation Angle (E/W): 5 degrees to 90 degrees

Azimuth (E/W): 0 degrees to 360 degrees

NOTE: The telecommand / telemetry carrier with designator 40K0G2D/70K0G7D are for GLOBALSTAR 2.0 satellites while the telecommand / telemetry carrier with designator 76K0F2D/7K00G1D are for current Globalstar satellites (Call Sign S2115).

Information on MLS Sites

For the Clifton, Texas, Globalstar gateway site, there are four potential MLS sites, i.e., Category III airports, within the 200 nautical mile coordination distance. The Clifton site is located at 31-48-0.2 N, 97-36-44.3 W. The airports are:

IAH	Houston – George Bush International Airport,		
	approximately 163 nautical miles from Clifton		
AUS	Austin – Bergstrom International Airport,		
	approximately 91 nautical miles away		
DFW	Dallas/Ft. Worth International Airport,		
	approximately 71 nautical miles away		
AFW	Ft. Worth Alliance Field, approximately 68		
	nautical miles away		

Based on a directory used for MLS coordination purposes, and to the best of its knowledge, GUSA believes that MLS is not active at any of those sites and will not be active during the requested 60-day extension of the STA period.